



P = 4 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
540	70	1.85	2.67	BG30-../D11MA4	46	1450	-	650	58	2.2
420	90	1.55	3.40	"	"	1580	-	510	74	1.9
340	112	1.55	4.21	"	"	1630	-	410	93	1.85
265	144	1.4	5.44	"	"	1670	-	315	121	1.65
215	177	1.25	6.75	"	"	1760	-	255	149	1.45
180	210	1.05	7.91	"	"	1760	-	220	173	1.25
166	230	1.05	8.60	"	"	2800	-	199	191	1.3
149	255	1.0	9.55	"	"	3000	-	180	210	1.2
134	285	0.93	10.65	"	"	2950	-	161	235	1.15
121	315	0.87	11.82	"	"	3200	-	145	260	1.05
104	365	0.81	13.77	"	"	3150	-	125	305	0.96
580	65	3.1	2.46	BG40-../D11MA4	65	2150	-	700	54	3.7
450	84	2.7	3.19	"	"	2350	-	540	70	3.2
360	106	2.3	3.97	"	"	2400	-	435	87	2.8
290	131	2.0	4.94	"	"	2450	-	350	109	2.5
230	166	1.8	6.29	"	"	2600	-	275	138	2.1
187	200	1.5	7.62	"	"	2650	-	225	169	1.75
171	220	1.55	8.31	"	"	4100	-	210	181	1.9
158	240	1.25	9.00	"	"	2650	-	190	200	1.5
154	245	1.45	9.23	"	"	4350	-	186	205	1.75
138	275	1.35	10.35	"	"	4350	-	166	230	1.65
124	305	1.3	11.49	"	"	4600	-	149	255	1.55
111	340	1.2	12.86	"	"	4500	-	133	285	1.45
100	380	1.1	14.28	"	"	4900	-	120	315	1.35
87	435	0.98	16.39	"	"	5300	-	105	360	1.2
79	480	0.89	18.19	"	"	5600	-	95	400	1.05
72	530	0.8	19.84	"	"	5800	-	87	435	0.98
290	131	3.0	4.91	BG50-../D11MA4	75	3500	-	350	109	3.7
215	177	2.6	6.74	"	"	3750	-	255	149	3.0
164	230	2.2	8.70	"	"	5300	-	197	193	2.6
148	255	2.1	9.65	"	"	5600	-	178	210	2.5
118	320	1.8	12.06	"	"	5700	-	142	265	2.2
107	355	1.65	13.36	"	"	6100	-	128	295	2.0
86	440	1.45	16.53	"	"	6500	-	104	365	1.75
78	485	1.3	18.33	"	"	7200	-	94	405	1.55
65	580	1.1	21.96	"	"	8000	-	78	485	1.3
59	640	0.98	24.34	"	"	8700	-	71	530	1.2
48	790	0.8	29.62	"	"	8000	-	58	650	0.97
117	325	3.0	12.16	BG60-../D11MA4	107	10800	-	141	270	3.7
106	360	2.8	13.47	"	"	11200	-	127	300	3.4
85	445	2.5	16.80	"	"	12000	-	102	370	3.0
77	495	2.3	18.62	"	"	12400	-	92	415	2.8
64	590	2.0	22.40	"	"	13300	-	77	495	2.4
58	650	1.85	24.82	"	"	13800	-	69	550	2.2
48.5	780	1.55	29.31	"	"	14800	-	59	640	1.9
44	860	1.4	32.48	"	"	15400	-	53	720	1.65
37	1030	1.15	38.85	"	"	16000	-	44.5	850	1.4
33	1150	1.05	43.05	"	"	16000	-	40	950	1.25
28.5	1340	0.9	50.31	"	"	16000	-	34	1120	1.05
25.5	1490	0.81	55.76	"	"	16000	-	31	1230	0.98
53	720	3.2	27.21	BG70-../D11MA4	138	16400	-	63	600	3.8
48	790	2.9	29.69	"	"	16900	-	58	650	3.5
40.5	940	2.4	35.24	"	"	18300	-	49	770	3.0
36.5	1040	2.2	39.22	"	"	19100	-	44	860	2.7
31	1230	1.85	46.54	"	"	20000	-	37	1030	2.2
28.5	1340	1.7	50.40	"	"	20000	-	34	1120	2.1
24	1590	1.45	59.82	"	"	20000	-	29	1310	1.75
22	1730	1.35	64.85	BG70Z-../D11MA4	164	20000	-	26.5	1440	1.6
19.5	1950	1.2	73.82	"	"	20000	-	23.5	1620	1.4
16.5	2300	1.0	87.61	"	"	20000	-	20	1910	1.2
15	2500	0.92	95.74	"	"	20000	-	18	2100	1.1


P = 4 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
29.5	1290	3.3	48.80	BG80-../D11MA4	192	23800	-	35.5	1070	3.9
25	1520	2.8	57.24	"	"	25400	-	30	1270	3.3
22.5	1690	2.5	63.56	"	"	26000	-	27	1410	3.0
21.5	1770	2.4	66.40	BG80Z-../D11MA4	234	26000	-	26	1460	2.9
19.5	1950	2.2	73.73	"	"	26000	-	23.5	1620	2.6
17	2200	1.9	84.55	"	"	26000	-	20.5	1860	2.3
15.5	2450	1.7	93.89	"	"	26000	-	18.5	2050	2.0
13	2900	1.45	112.4	"	"	26000	-	15.5	2450	1.7
11.5	3300	1.25	124.8	"	"	26000	-	14	2700	1.55
9.8	3850	1.1	145.4	"	"	26000	-	12	3150	1.35
8.8	4300	0.98	161.5	"	"	26000	-	11	3450	1.2
7.7	4950	0.85	186.8	"	"	26000	-	9.2	4150	1.0
6.3	5700	0.81	227.2	BG80G40-../D11MA4	242	26000	-	7.6	4700	0.98
13.5	2800	3.0	105.7	BG90Z-../D11MA4	336	65000	-	16.5	2300	3.7
11.5	3300	2.5	127.1	"	"	65000	-	13.5	2800	3.0
10.5	3600	2.3	139.2	"	"	65000	-	12.5	3050	2.8
8.8	4300	1.95	163.0	"	"	65000	-	10.5	3600	2.3
8.0	4750	1.75	178.5	"	"	65000	-	9.6	3950	2.1
6.9	5500	1.55	208.3	"	"	65000	-	8.3	4600	1.85
6.3	6000	1.4	228.1	"	"	65000	-	7.5	5000	1.7
5.5	6500	1.4	262.5	BG90G50-../D11MA4	353	65000	-	6.6	5300	1.75
4.8	7600	1.2	298.8	"	"	65000	-	5.8	6300	1.45
4.0	9000	1.0	360.3	"	"	65000	-	4.8	7400	1.25
3.3	11100	0.83	435.8	"	"	65000	-	4.0	9100	1.0
7.2	5300	3.2	198.8	BG100-../D11MA4	453	90000	-	8.7	4350	3.9
6.2	6100	2.8	232.6	"	"	90000	-	7.4	5100	3.3
5.5	6900	2.4	259.0	"	"	90000	-	6.7	5700	2.9
5.3	7200	2.6	269.8	BG100Z-../D11MA4	543	90000	-	6.4	5900	3.1
4.8	7900	2.3	300.4	"	"	90000	-	5.7	6700	2.8
4.2	9000	2.1	343.6	"	"	90000	-	5.0	7600	2.4
3.8	10000	1.85	382.6	"	"	90000	-	4.5	8400	2.2
3.2	11900	1.55	456.7	"	"	90000	-	3.8	10000	1.85
2.8	13600	1.35	508.5	"	"	90000	-	3.4	11200	1.65
2.5	15200	1.2	591.1	"	"	90000	-	2.9	13100	1.4
2.2	17300	1.05	658.1	"	"	90000	-	2.6	14600	1.25
1.9	20100	0.92	759.0	"	"	90000	-	2.3	16600	1.1
1.7	22400	0.83	845.1	"	"	90000	-	2.1	18100	1.0


P = 5.5 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
540	97	1.3	2.67	BG30-../D11LA4	58	1450	-	650	80	1.6
420	125	1.1	3.40	"	"	1580	-	510	102	1.35
340	154	1.1	4.21	"	"	1630	-	410	128	1.35
265	198	1.0	5.44	"	"	1670	-	315	166	1.2
215	240	0.9	6.75	"	"	1760	-	255	205	1.05
580	90	2.2	2.46	BG40-../D11LA4	77	2150	-	700	75	2.7
450	116	1.95	3.19	"	"	2350	-	540	97	2.3
360	145	1.7	3.97	"	"	2400	-	435	120	2.0
290	181	1.5	4.94	"	"	2450	-	350	150	1.8
230	225	1.3	6.29	"	"	2600	-	275	191	1.55
187	280	1.05	7.62	"	"	2650	-	225	230	1.3
171	305	1.15	8.31	"	"	4100	-	210	250	1.4
158	330	0.89	9.00	"	"	2650	-	190	275	1.05
154	340	1.05	9.23	"	"	4350	-	186	280	1.3
138	380	0.99	10.35	"	"	4350	-	166	315	1.2
124	420	0.93	11.49	"	"	4600	-	149	350	1.1

P = 5.5 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
111	470	0.87	12.86	BG40-../D11LA4	"	4500	-	133	390	1.05
100	520	0.81	14.28	"	"	4900	-	120	435	0.97
400	131	2.6	3.55	BG50-../D11LA4	86	3300	-	485	108	3.2
290	181	2.2	4.91	"	"	3500	-	350	150	2.7
215	240	1.9	6.74	"	"	3750	-	255	205	2.2
164	320	1.6	8.70	"	"	5300	-	197	265	1.9
148	350	1.5	9.65	"	"	5600	-	178	295	1.8
118	445	1.3	12.06	"	"	5700	-	142	365	1.6
107	490	1.2	13.36	"	"	6100	-	128	410	1.45
86	610	1.05	16.53	"	"	6500	-	104	500	1.25
78	670	0.94	18.33	"	"	7200	-	94	550	1.15
210	250	3.1	6.88	BG60-../D11LA4	119	8600	-	250	210	3.7
156	335	2.7	9.13	"	"	9800	-	188	275	3.2
141	370	2.5	10.12	"	"	10200	-	169	310	2.9
117	445	2.2	12.16	"	"	10800	-	141	370	2.7
106	495	2.1	13.47	"	"	11200	-	127	410	2.5
85	610	1.8	16.80	"	"	12000	-	102	510	2.2
77	680	1.7	18.62	"	"	12400	-	92	570	2.0
64	820	1.45	22.40	"	"	13300	-	77	680	1.75
58	900	1.35	24.82	"	"	13800	-	69	760	1.6
48.5	1080	1.1	29.31	"	"	14800	-	59	890	1.35
44	1190	1.0	32.48	"	"	15400	-	53	990	1.2
37	1410	0.85	38.85	"	"	16000	-	44.5	1180	1.0
68	770	3.0	20.98	BG70-../D11LA4	149	14600	-	82	640	3.6
62	840	2.7	22.92	"	"	15100	-	75	700	3.3
53	990	2.3	27.21	"	"	16400	-	63	830	2.8
48	1090	2.1	29.69	"	"	16900	-	58	900	2.6
40.5	1290	1.8	35.24	"	"	18300	-	49	1070	2.1
36.5	1430	1.6	39.22	"	"	19100	-	44	1190	1.95
31	1690	1.35	46.54	"	"	20000	-	37	1410	1.65
28.5	1840	1.25	50.40	"	"	20000	-	34	1540	1.5
24	2150	1.05	59.82	"	"	20000	-	29	1810	1.25
22	2350	0.98	64.85	BG70Z-../D11LA4	176	20000	-	26.5	1980	1.15
19.5	2650	0.87	73.82	"	"	20000	-	23.5	2200	1.05
41.5	1260	3.3	34.22	BG80-../D11LA4	204	20200	-	50	1050	4.0
37.5	1400	3.0	38.00	"	"	21300	-	45	1160	3.6
32.5	1610	2.6	43.94	"	"	22600	-	39	1340	3.1
29.5	1780	2.4	48.80	"	"	23800	-	35.5	1470	2.9
25	2100	2.0	57.24	"	"	25400	-	30	1750	2.4
22.5	2300	1.85	63.56	"	"	26000	-	27	1940	2.2
21.5	2400	1.75	66.40	BG80Z-../D11LA4	246	26000	-	26	2000	2.1
19.5	2650	1.6	73.73	"	"	26000	-	23.5	2200	1.9
17	3050	1.4	84.55	"	"	26000	-	20.5	2550	1.65
15.5	3350	1.25	93.89	"	"	26000	-	18.5	2800	1.5
13	4000	1.05	112.4	"	"	26000	-	15.5	3350	1.25
11.5	4550	0.92	124.8	"	"	26000	-	14	3750	1.1
25	2100	3.2	57.04	BG90Z-../D11LA4	348	65000	-	30	1750	3.9
23	2250	3.3	62.47	"	"	65000	-	27.5	1910	3.9
19	2750	3.1	76.61	"	"	65000	-	22.5	2300	3.7
17	3050	2.8	83.91	"	"	65000	-	20.5	2550	3.3
15	3500	2.4	96.53	"	"	65000	-	18	2900	2.9
13.5	3850	2.2	105.7	"	"	65000	-	16.5	3150	2.7
11.5	4550	1.85	127.1	"	"	65000	-	13.5	3850	2.2
10.5	5000	1.7	139.2	"	"	65000	-	12.5	4200	2.0
8.8	5900	1.4	163.0	"	"	65000	-	10.5	5000	1.7
8.0	6500	1.3	178.5	"	"	65000	-	9.6	5400	1.55
6.9	7600	1.1	208.3	"	"	65000	-	8.3	6300	1.35
6.3	8300	1.0	228.1	"	"	65000	-	7.5	7000	1.2
5.5	9100	1.0	262.5	BG90G50-../D11LA4	365	65000	-	6.6	7500	1.25
4.8	10600	0.87	298.8	"	"	65000	-	5.8	8700	1.05


P = 5.5 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
9.2	5700	2.9	154.8	BG100-../D11LA4	465	90000	-	11.5	4550	3.7
8.0	6500	2.6	178.6	"	"	90000	-	9.6	5400	3.1
7.2	7200	2.3	198.8	"	"	90000	-	8.7	6000	2.8
6.2	8400	2.0	232.6	"	"	90000	-	7.4	7000	2.4
5.5	9500	1.75	259.0	"	"	90000	-	6.7	7800	2.2
5.3	9900	1.85	269.8	BG100Z-../D11LA4	555	90000	-	6.4	8200	2.3
4.8	10900	1.7	300.4	"	"	90000	-	5.7	9200	2.0
4.2	12500	1.5	343.6	"	"	90000	-	5.0	10500	1.75
3.8	13800	1.35	382.6	"	"	90000	-	4.5	11600	1.6
3.2	16400	1.15	456.7	"	"	90000	-	3.8	13800	1.35
2.8	18700	0.99	508.5	"	"	90000	-	3.4	15400	1.2
2.5	21000	0.88	591.1	"	"	90000	-	2.9	18100	1.0

P = 7.5 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
580	123	2.5	2.47	BG50-../D13MA4	98	2900	-	700	102	3.0
400	179	1.95	3.55	"	"	3300	-	485	147	2.4
290	245	1.6	4.91	"	"	3500	-	350	200	2.0
215	330	1.35	6.74	"	"	3750	-	255	280	1.6
164	435	1.15	8.70	"	"	5300	-	197	360	1.4
148	480	1.1	9.65	"	"	5600	-	178	400	1.3
118	600	0.96	12.06	"	"	5700	-	142	500	1.15
107	660	0.9	13.36	"	"	6100	-	128	550	1.1
380	188	3.3	3.74	BG60-../D13MA4	132	7100	-	460	155	3.9
290	245	2.8	4.98	"	"	7800	-	345	205	3.4
210	340	2.3	6.88	"	"	8600	-	250	285	2.7
156	455	1.95	9.13	"	"	9800	-	188	380	2.3
141	500	1.8	10.12	"	"	10200	-	169	420	2.2
117	610	1.6	12.16	"	"	10800	-	141	500	2.0
106	670	1.5	13.47	"	"	11200	-	127	560	1.8
85	840	1.3	16.80	"	"	12000	-	102	700	1.6
77	930	1.25	18.62	"	"	12400	-	92	770	1.5
64	1110	1.1	22.40	"	"	13300	-	77	930	1.3
58	1230	0.98	24.82	"	"	13800	-	69	1030	1.15
48.5	1470	0.82	29.31	"	"	14800	-	59	1210	0.99
92	770	3.0	15.53	BG70-../D13MA4	162	12700	-	111	640	3.6
81	880	2.6	17.68	"	"	13400	-	97	730	3.2
68	1050	2.2	20.98	"	"	14600	-	82	870	2.6
62	1150	2.0	22.92	"	"	15100	-	75	950	2.4
53	1350	1.7	27.21	"	"	16400	-	63	1130	2.0
48	1490	1.55	29.69	"	"	16900	-	58	1230	1.85
40.5	1760	1.3	35.24	"	"	18300	-	49	1460	1.6
36.5	1960	1.15	39.22	"	"	19100	-	44	1620	1.4
31	2300	1.0	46.54	"	"	20000	-	37	1930	1.2
28.5	2500	0.92	50.40	"	"	20000	-	34	2100	1.1
54	1320	3.2	26.44	BG80-../D13MA4	216	17900	-	65	1100	3.8
48.5	1470	2.9	29.36	"	"	18900	-	59	1210	3.5
41.5	1720	2.4	34.22	"	"	20200	-	50	1430	2.9
37.5	1910	2.2	38.00	"	"	21300	-	45	1590	2.6
32.5	2200	1.9	43.94	"	"	22600	-	39	1830	2.3
29.5	2400	1.75	48.80	"	"	23800	-	35.5	2000	2.1
25	2850	1.45	57.24	"	"	25400	-	30	2350	1.8
22.5	3150	1.35	63.56	"	"	26000	-	27	2650	1.6
21.5	3300	1.25	66.40	BG80Z-../D13MA4	259	26000	-	26	2750	1.55
19.5	3650	1.15	73.73	"	"	26000	-	23.5	3000	1.4
17	4200	1.0	84.55	"	"	26000	-	20.5	3450	1.2
15.5	4600	0.91	93.89	"	"	26000	-	18.5	3850	1.1
27	2650	3.2	53.46	BG90-../D13MA4	305	65000	-	32	2200	3.8

P = 7.5 кВт




50 Hz			i	Typ	m	F _{RN}	F _{RV}	60 Hz		
n ₂ 1/min	M ₂ Nm	f _B						n ₂ 1/min	M ₂ Nm	f _B
25	2850	2.4	57.04	BG90Z-../D13MA4	361	65000	-	30	2350	2.9
23	3100	2.4	62.47	"	"	65000	-	27.5	2600	2.9
19	3750	2.2	76.61	"	"	65000	-	22.5	3150	2.7
17	4200	2.0	83.91	"	"	65000	-	20.5	3450	2.4
15	4750	1.75	96.53	"	"	65000	-	18	3950	2.1
13.5	5300	1.6	105.7	"	"	65000	-	16.5	4300	1.95
11.5	6200	1.35	127.1	"	"	65000	-	13.5	5300	1.6
10.5	6800	1.25	139.2	"	"	65000	-	12.5	5700	1.45
8.8	8100	1.05	163.0	"	"	65000	-	10.5	6800	1.25
8.0	8900	0.94	178.5	"	"	65000	-	9.6	7400	1.15
6.9	10300	0.82	208.3	"	"	65000	-	8.3	8600	0.98
6.5	10700	0.86	219.9	BG90G50-../D13MA4	377	65000	-	7.8	8800	1.05
13.5	5300	3.2	107.5	BG100-../D13MA4	477	90000	-	16	4450	3.8
12	5900	2.8	119.7	"	"	90000	-	14.5	4900	3.4
10.5	6800	2.5	139.1	"	"	90000	-	12.5	5700	2.9
9.2	7700	2.2	154.8	"	"	90000	-	11.5	6200	2.7
8.0	8900	1.9	178.6	"	"	90000	-	9.6	7400	2.3
7.2	9900	1.7	198.8	"	"	90000	-	8.7	8200	2.0
6.2	11500	1.45	232.6	"	"	90000	-	7.4	9600	1.75
5.5	13000	1.3	259.0	"	"	90000	-	6.7	10600	1.6
5.3	13500	1.35	269.8	BG100Z-../D13MA4	568	90000	-	6.4	11100	1.65
4.8	14900	1.25	300.4	"	"	90000	-	5.7	12500	1.5
4.2	17000	1.1	343.6	"	"	90000	-	5.0	14300	1.3
3.8	18800	0.98	382.6	"	"	90000	-	4.5	15900	1.15
3.2	22300	0.83	456.7	"	"	90000	-	3.8	18800	0.98

P = 9.5 кВт

50 Hz			i	Typ	m	F _{RN}	F _{RV}	60 Hz		
n ₂ 1/min	M ₂ Nm	f _B						n ₂ 1/min	M ₂ Nm	f _B
580	156	1.95	2.47	BG50-../D13LA4	101	2900	-	700	129	2.4
400	225	1.55	3.55	"	"	3300	-	485	187	1.85
290	310	1.3	4.91	"	"	3500	-	350	255	1.55
215	420	1.1	6.74	"	"	3750	-	255	355	1.25
164	550	0.92	8.70	"	"	5300	-	197	460	1.1
148	610	0.86	9.65	"	"	5600	-	178	500	1.05
380	235	2.6	3.74	BG60-../D13LA4	135	7100	-	460	197	3.1
290	310	2.2	4.98	"	"	7800	-	345	260	2.7
210	430	1.8	6.88	"	"	8600	-	250	360	2.2
156	580	1.55	9.13	"	"	9800	-	188	480	1.85
141	640	1.45	10.12	"	"	10200	-	169	530	1.7
117	770	1.3	12.16	"	"	10800	-	141	640	1.55
106	850	1.2	13.47	"	"	11200	-	127	710	1.45
85	1060	1.05	16.80	"	"	12000	-	102	880	1.25
77	1170	0.98	18.62	"	"	12400	-	92	980	1.15
64	1410	0.85	22.40	"	"	13300	-	77	1170	1.05
119	760	3.0	11.97	BG70-../D13LA4	165	11200	-	143	630	3.7
109	830	2.8	13.08	"	"	11600	-	131	690	3.3
92	980	2.3	15.53	"	"	12700	-	111	810	2.8
81	1120	2.1	17.68	"	"	13400	-	97	930	2.5
68	1330	1.75	20.98	"	"	14600	-	82	1100	2.1
62	1460	1.6	22.92	"	"	15100	-	75	1200	1.9
53	1710	1.35	27.21	"	"	16400	-	63	1440	1.6
48	1890	1.2	29.69	"	"	16900	-	58	1560	1.45
40.5	2200	1.05	35.24	"	"	18300	-	49	1850	1.25
36.5	2450	0.94	39.22	"	"	19100	-	44	2050	1.1
72	1260	3.3	19.89	BG80-../D13LA4	219	15500	-	86	1050	4.0
65	1390	3.0	22.09	"	"	16500	-	78	1160	3.6
54	1680	2.5	26.44	"	"	17900	-	65	1390	3.0
48.5	1870	2.2	29.36	"	"	18900	-	59	1530	2.7
41.5	2150	1.95	34.22	"	"	20200	-	50	1810	2.3

P = 9.5 кВт




50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
37.5	2400	1.75	38.00	BG80-../D13LA4	"	21300	-	45	2000	2.1
32.5	2750	1.55	43.94	"	"	22600	-	39	2300	1.85
29.5	3050	1.4	48.80	"	"	23800	-	35.5	2550	1.65
25	3600	1.15	57.24	"	"	25400	-	30	3000	1.4
22.5	4000	1.05	63.56	"	"	26000	-	27	3350	1.25
21.5	4200	1.0	66.40	BG80Z-../D13LA4	262	26000	-	26	3450	1.2
19.5	4650	0.9	73.73	"	"	26000	-	23.5	3850	1.1
34	2650	3.2	41.85	BG90-../D13LA4	308	65000	-	41	2200	3.8
29.5	3050	2.8	48.82	"	"	65000	-	35.5	2550	3.3
27	3350	2.5	53.46	"	"	65000	-	32	2800	3.0
25	3600	1.9	57.04	BG90Z-../D13LA4	364	65000	-	30	3000	2.3
23	3900	1.9	62.47	"	"	65000	-	27.5	3250	2.3
19	4750	1.75	76.61	"	"	65000	-	22.5	4000	2.1
17	5300	1.6	83.91	"	"	65000	-	20.5	4400	1.9
15	6000	1.4	96.53	"	"	65000	-	18	5000	1.7
13.5	6700	1.25	105.7	"	"	65000	-	16.5	5400	1.55
11.5	7800	1.1	127.1	"	"	65000	-	13.5	6700	1.25
10.5	8600	0.98	139.2	"	"	65000	-	12.5	7200	1.15
8.8	10300	0.82	163.0	"	"	65000	-	10.5	8600	0.98
18	5000	3.3	80.85	BG100-../D13LA4	480	90000	-	21.5	4200	3.9
16	5600	3.0	90.02	"	"	90000	-	19	4750	3.5
13.5	6700	2.5	107.5	"	"	90000	-	16	5600	3.0
12	7500	2.2	119.7	"	"	90000	-	14.5	6200	2.7
10.5	8600	1.95	139.1	"	"	90000	-	12.5	7200	2.3
9.2	9800	1.7	154.8	"	"	90000	-	11.5	7800	2.2
8.0	11300	1.5	178.6	"	"	90000	-	9.6	9400	1.8
7.2	12600	1.35	198.8	"	"	90000	-	8.7	10400	1.6
6.2	14600	1.15	232.6	"	"	90000	-	7.4	12200	1.4
5.5	16400	1.0	259.0	"	"	90000	-	6.7	13500	1.25
5.3	17100	1.1	269.8	BG100Z-../D13LA4	571	90000	-	6.4	14100	1.3
4.8	18900	0.98	300.4	"	"	90000	-	5.7	15900	1.15
4.2	21600	0.86	343.6	"	"	90000	-	5.0	18100	1.0

P = 11 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
600	175	1.75	2.47	BG50-../D16MA4	146	2900	-	720	145	2.1
415	250	1.4	3.55	"	"	3300	-	500	210	1.65
300	350	1.15	4.91	"	"	3500	-	360	290	1.35
220	475	0.95	6.74	"	"	3750	-	265	395	1.15
168	620	0.82	8.70	"	"	5300	-	205	510	1.0
580	181	3.0	2.52	BG60-../D16MA4	180	6200	-	700	150	3.6
395	265	2.3	3.74	"	"	7100	-	475	220	2.8
295	355	1.95	4.98	"	"	7800	-	355	295	2.3
215	485	1.6	6.88	"	"	8600	-	260	400	1.95
160	650	1.35	9.13	"	"	9800	-	193	540	1.65
145	720	1.25	10.12	"	"	10200	-	174	600	1.5
121	860	1.15	12.16	"	"	10800	-	145	720	1.35
109	960	1.05	13.47	"	"	11200	-	131	800	1.3
87	1200	0.92	16.80	"	"	12000	-	105	1000	1.1
79	1320	0.87	18.62	"	"	12400	-	95	1100	1.05
145	720	3.2	10.09	BG70-../D16MA4	214	10200	-	175	600	3.8
122	860	2.7	11.97	"	"	11200	-	148	700	3.3
112	930	2.5	13.08	"	"	11600	-	135	770	3.0
95	1100	2.1	15.53	"	"	12700	-	114	920	2.5
83	1260	1.85	17.68	"	"	13400	-	100	1050	2.2
70	1500	1.55	20.98	"	"	14600	-	84	1250	1.85
64	1640	1.4	22.92	"	"	15100	-	77	1360	1.7
54	1940	1.2	27.21	"	"	16400	-	65	1610	1.45
49.5	2100	1.1	29.69	"	"	16900	-	60	1750	1.3


P = 11 кВт



50 Hz			i	Typ	m	F _{RN}	F _{RV}	60 Hz		
n ₂ 1/min	M ₂ Nm	f _B						n ₂ 1/min	M ₂ Nm	f _B
41.5	2500	0.92	35.24	BG70-../D16MA4	"	18300	-	50	2100	1.1
37.5	2800	0.82	39.22	"	"	19100	-	45	2300	1.0
74	1410	3.0	19.89	BG80-../D16MA4	264	15500	-	89	1180	3.6
67	1560	2.7	22.09	"	"	16500	-	80	1310	3.2
56	1870	2.2	26.44	"	"	17900	-	67	1560	2.7
50	2100	2.0	29.36	"	"	18900	-	60	1750	2.4
43	2400	1.75	34.22	"	"	20200	-	52	2000	2.1
38.5	2700	1.55	38.00	"	"	21300	-	46.5	2250	1.85
33.5	3100	1.35	43.94	"	"	22600	-	40.5	2550	1.65
30	3500	1.2	48.80	"	"	23800	-	36.5	2850	1.45
26	4000	1.05	57.24	"	"	25400	-	31	3350	1.25
23	4550	0.92	63.56	"	"	26000	-	28	3750	1.1
22	4750	0.88	66.40	BG80Z-../D16MA4	307	26000	-	27	3850	1.1
20	5200	0.81	73.73	"	"	26000	-	24	4350	0.97
38.5	2700	3.1	38.21	BG90-../D16MA4	354	65000	-	46.5	2250	3.7
35	3000	2.8	41.85	"	"	65000	-	42.5	2450	3.4
30	3500	2.4	48.82	"	"	65000	-	36.5	2850	2.9
27.5	3800	2.2	53.46	"	"	65000	-	33	3150	2.7
26	4000	1.7	57.04	BG90Z-../D16MA4	413	65000	-	31	3350	2.0
23.5	4450	1.7	62.47	"	"	65000	-	28.5	3650	2.1
19.5	5300	1.6	76.61	"	"	65000	-	23	4550	1.85
17.5	6000	1.4	83.91	"	"	65000	-	21	5000	1.7
15.5	6700	1.25	96.53	"	"	65000	-	18.5	5600	1.5
14	7500	1.1	105.7	"	"	65000	-	17	6100	1.4
11.5	9100	0.92	127.1	"	"	65000	-	14	7500	1.1
10.5	10000	0.84	139.2	"	"	65000	-	13	8000	1.05
21	5000	3.2	70.69	BG100-../D16MA4	524	90000	-	25	4200	3.8
18.5	5600	3.0	80.85	"	"	90000	-	22	4750	3.5
16.5	6300	2.7	90.02	"	"	90000	-	20	5200	3.2
14	7500	2.2	107.5	"	"	90000	-	16.5	6300	2.7
12.5	8400	2.0	119.7	"	"	90000	-	15	7000	2.4
10.5	10000	1.7	139.1	"	"	90000	-	13	8000	2.1
9.5	11000	1.55	154.8	"	"	90000	-	11.5	9100	1.85
8.2	12800	1.3	178.6	"	"	90000	-	9.9	10600	1.6
7.4	14100	1.2	198.8	"	"	90000	-	8.9	11800	1.4
6.3	16600	1.0	232.6	"	"	90000	-	7.6	13800	1.2
5.7	18400	0.91	259.0	"	"	90000	-	6.8	15400	1.1
5.5	19100	0.97	269.8	BG100Z-../D16MA4	616	90000	-	6.6	15900	1.15
4.9	21400	0.86	300.4	"	"	90000	-	5.9	17800	1.05

P = 15 кВт

50 Hz			i	Typ	m	F _{RN}	F _{RV}	60 Hz		
n ₂ 1/min	M ₂ Nm	f _B						n ₂ 1/min	M ₂ Nm	f _B
600	235	1.3	2.47	BG50-../D16LA4	159	2900	-	720	198	1.55
415	345	1.0	3.55	"	"	3300	-	500	285	1.2
300	475	0.84	4.91	"	"	3500	-	360	395	1.0
580	245	2.2	2.52	BG60-../D16LA4	193	6200	-	700	200	2.7
395	360	1.7	3.74	"	"	7100	-	475	300	2.0
295	485	1.4	4.98	"	"	7800	-	355	400	1.7
215	660	1.2	6.88	"	"	8600	-	260	550	1.4
160	890	1.0	9.13	"	"	9800	-	193	740	1.2
145	980	0.93	10.12	"	"	10200	-	174	820	1.1
121	1180	0.84	12.16	"	"	10800	-	145	980	1.0
205	690	3.1	7.14	BG70-../D16LA4	228	8800	-	250	570	3.8
173	820	2.8	8.48	"	"	9500	-	210	680	3.4
145	980	2.3	10.09	"	"	10200	-	175	810	2.8
122	1170	1.95	11.97	"	"	11200	-	148	960	2.4
112	1270	1.8	13.08	"	"	11600	-	135	1060	2.2


P = 15 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
95	1500	1.55	15.53	BG70-../D16LA4	"	12700	-	114	1250	1.85
83	1720	1.35	17.68	"	"	13400	-	100	1430	1.6
70	2000	1.15	20.98	"	"	14600	-	84	1700	1.35
64	2200	1.05	22.92	"	"	15100	-	77	1860	1.25
54	2650	0.87	27.21	"	"	16400	-	65	2200	1.05
49.5	2850	0.81	29.69	"	"	16900	-	60	2350	0.98
94	1520	2.8	15.62	BG80-../D16LA4	276	13700	-	113	1260	3.3
85	1680	2.5	17.35	"	"	14600	-	102	1400	3.0
74	1930	2.2	19.89	"	"	15500	-	89	1600	2.6
67	2100	2.0	22.09	"	"	16500	-	80	1790	2.3
56	2550	1.65	26.44	"	"	17900	-	67	2100	2.0
50	2850	1.45	29.36	"	"	18900	-	60	2350	1.8
43	3300	1.25	34.22	"	"	20200	-	52	2750	1.55
38.5	3700	1.15	38.00	"	"	21300	-	46.5	3050	1.4
33.5	4250	0.99	43.94	"	"	22600	-	40.5	3500	1.2
30	4750	0.88	48.80	"	"	23800	-	36.5	3900	1.1
49.5	2850	2.9	29.78	BG90-../D16LA4	367	65000	-	60	2350	3.6
45	3150	2.7	32.62	"	"	65000	-	54	2650	3.2
38.5	3700	2.3	38.21	"	"	65000	-	46.5	3050	2.8
35	4050	2.1	41.85	"	"	65000	-	42.5	3350	2.5
30	4750	1.75	48.82	"	"	65000	-	36.5	3900	2.2
27.5	5200	1.6	53.46	"	"	65000	-	33	4300	1.95
26	5500	1.25	57.04	BG90Z-../D16LA4	426	65000	-	31	4600	1.5
23.5	6000	1.25	62.47	"	"	65000	-	28.5	5000	1.5
19.5	7300	1.15	76.61	"	"	65000	-	23	6200	1.35
17.5	8100	1.05	83.91	"	"	65000	-	21	6800	1.25
15.5	9200	0.91	96.53	"	"	65000	-	18.5	7700	1.1
14	10200	0.82	105.7	"	"	65000	-	17	8400	1.0
31.5	4500	3.1	46.43	BG100-../D16LA4	538	90000	-	38	3750	3.8
28.5	5000	2.9	51.70	"	"	90000	-	34.5	4150	3.5
23	6200	2.5	63.49	"	"	90000	-	28	5100	3.0
21	6800	2.3	70.69	"	"	90000	-	25	5700	2.8
18.5	7700	2.1	80.85	"	"	90000	-	22	6500	2.5
16.5	8600	1.95	90.02	"	"	90000	-	20	7100	2.4
14	10200	1.65	107.5	"	"	90000	-	16.5	8600	1.95
12.5	11400	1.45	119.7	"	"	90000	-	15	9500	1.75
10.5	13600	1.25	139.1	"	"	90000	-	13	11000	1.55
9.5	15000	1.1	154.8	"	"	90000	-	11.5	12400	1.35
8.2	17400	0.97	178.6	"	"	90000	-	9.9	14400	1.15
7.4	19300	0.87	198.8	"	"	90000	-	8.9	16000	1.05

P = 18.5 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
600	290	1.05	2.47	BG50-../D16XA4	169	2900	-	720	245	1.25
415	425	0.82	3.55	"	"	3300	-	500	350	0.99
580	300	1.8	2.52	BG60-../D16XA4	203	6200	-	700	250	2.1
395	445	1.4	3.74	"	"	7100	-	475	370	1.65
295	590	1.15	4.98	"	"	7800	-	355	495	1.4
215	820	0.95	6.88	"	"	8600	-	260	670	1.15
160	1100	0.81	9.13	"	"	9800	-	193	910	0.98
205	860	2.5	7.14	BG70-../D16XA4	238	8800	-	250	700	3.1
173	1020	2.2	8.48	"	"	9500	-	210	840	2.7
145	1210	1.9	10.09	"	"	10200	-	175	1000	2.3
122	1440	1.6	11.97	"	"	11200	-	148	1190	1.95
112	1570	1.45	13.08	"	"	11600	-	135	1300	1.75
95	1850	1.25	15.53	"	"	12700	-	114	1540	1.5
83	2100	1.1	17.68	"	"	13400	-	100	1760	1.3


P = 18,5 кВт



50 Hz			i	Typ	m	F _{RN}	F _{RV}	60 Hz		
n ₂ 1/min	M ₂ Nm	f _B						n ₂ 1/min	M ₂ Nm	f _B
70	2500	0.92	20.98	BG70-../D16XA4	"	14600	-	84	2100	1.1
64	2750	0.84	22.92	"	"	15100	-	77	2250	1.0
128	1380	3.0	11.43	BG80-../D16XA4	286	11600	-	154	1140	3.7
116	1520	2.8	12.69	"	"	12400	-	139	1270	3.3
94	1870	2.2	15.62	"	"	13700	-	113	1560	2.7
85	2050	2.0	17.35	"	"	14600	-	102	1730	2.4
74	2350	1.8	19.89	"	"	15500	-	89	1980	2.1
67	2600	1.6	22.09	"	"	16500	-	80	2200	1.9
56	3150	1.35	26.44	"	"	17900	-	67	2600	1.6
50	3500	1.2	29.36	"	"	18900	-	60	2900	1.45
43	4100	1.0	34.22	"	"	20200	-	52	3350	1.25
38.5	4550	0.92	38.00	"	"	21300	-	46.5	3750	1.1
33.5	5200	0.81	43.94	"	"	22600	-	40.5	4350	0.97
65	2700	3.1	22.62	BG90-../D16XA4	377	65000	-	78	2250	3.7
59	2950	2.8	24.78	"	"	65000	-	72	2450	3.4
49.5	3550	2.4	29.78	"	"	65000	-	60	2900	2.9
45	3900	2.2	32.62	"	"	65000	-	54	3250	2.6
38.5	4550	1.85	38.21	"	"	65000	-	46.5	3750	2.2
35	5000	1.7	41.85	"	"	65000	-	42.5	4150	2.0
30	5800	1.45	48.82	"	"	65000	-	36.5	4800	1.75
27.5	6400	1.3	53.46	"	"	65000	-	33	5300	1.6
26	6700	1.0	57.04	BG90Z-../D16XA4	436	65000	-	31	5600	1.2
23.5	7500	1.0	62.47	"	"	65000	-	28.5	6100	1.25
19.5	9000	0.93	76.61	"	"	65000	-	23	7600	1.1
17.5	10000	0.84	83.91	"	"	65000	-	21	8400	1.0
31.5	5600	2.5	46.43	BG100-../D16XA4	548	90000	-	38	4600	3.1
28.5	6100	2.4	51.70	"	"	90000	-	34.5	5100	2.8
23	7600	2.0	63.49	"	"	90000	-	28	6300	2.4
21	8400	1.9	70.69	"	"	90000	-	25	7000	2.3
18.5	9500	1.75	80.85	"	"	90000	-	22	8000	2.1
16.5	10700	1.55	90.02	"	"	90000	-	20	8800	1.9
14	12600	1.35	107.5	"	"	90000	-	16.5	10700	1.55
12.5	14100	1.2	119.7	"	"	90000	-	15	11700	1.45
10.5	16800	1.0	139.1	"	"	90000	-	13	13500	1.25
9.5	18500	0.91	154.8	"	"	90000	-	11.5	15300	1.1

P = 22 кВт

50 Hz			i	Typ	m	F _{RN}	F _{RV}	60 Hz		
n ₂ 1/min	M ₂ Nm	f _B						n ₂ 1/min	M ₂ Nm	f _B
295	710	2.1	4.95	BG70-../D18LA4	294	6900	-	360	580	2.6
250	840	2.1	5.87	"	"	8200	-	300	700	2.5
205	1020	2.1	7.14	"	"	8800	-	250	840	2.6
173	1210	1.9	8.48	"	"	9500	-	210	1000	2.3
145	1440	1.6	10.09	"	"	10200	-	175	1200	1.9
122	1720	1.35	11.97	"	"	11200	-	148	1410	1.65
112	1870	1.25	13.08	"	"	11600	-	135	1550	1.5
95	2200	1.05	15.53	"	"	12700	-	114	1840	1.25
83	2500	0.92	17.68	"	"	13400	-	100	2100	1.1
250	840	3.2	5.94	BG80-../D18LA4	348	8300	-	300	700	3.8
225	930	3.2	6.60	"	"	9100	-	270	770	3.8
176	1190	3.2	8.30	"	"	10400	-	215	970	3.9
159	1320	3.0	9.21	"	"	10800	-	192	1090	3.6
128	1640	2.6	11.43	"	"	11600	-	154	1360	3.1
116	1810	2.3	12.69	"	"	12400	-	139	1510	2.8
94	2200	1.9	15.62	"	"	13700	-	113	1850	2.3
85	2450	1.7	17.35	"	"	14600	-	102	2050	2.0
74	2800	1.5	19.89	"	"	15500	-	89	2350	1.8


P = 22 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
67	3100	1.35	22.09	BG80-../D18LA4	"	16500	-	80	2600	1.6
56	3750	1.1	26.44	"	"	17900	-	67	3100	1.35
50	4200	1.0	29.36	"	"	18900	-	60	3500	1.2
43	4850	0.87	34.22	"	"	20200	-	52	4000	1.05
82	2550	3.2	17.96	BG90-../D18LA4	440	59800	-	98	2100	3.9
75	2800	3.0	19.67	"	"	62400	-	90	2300	3.7
65	3200	2.6	22.62	"	"	65000	-	78	2650	3.2
59	3550	2.4	24.78	"	"	65000	-	72	2900	2.9
49.5	4200	2.0	29.78	"	"	65000	-	60	3500	2.4
45	4650	1.8	32.62	"	"	65000	-	54	3850	2.2
38.5	5400	1.55	38.21	"	"	65000	-	46.5	4500	1.85
35	6000	1.4	41.85	"	"	65000	-	42.5	4900	1.7
30	7000	1.2	48.82	"	"	65000	-	36.5	5700	1.45
27.5	7600	1.1	53.46	"	"	65000	-	33	6300	1.35
26	8000	0.85	57.04	BG90Z-../D18LA4	493	65000	-	31	6700	1.0
23.5	8900	0.84	62.47	"	"	65000	-	28.5	7300	1.05
61	3400	3.3	23.95	BG100-../D18LA4	609	87900	-	74	2800	4.0
43.5	4800	2.7	33.71	"	"	88500	-	53	3950	3.3
39	5300	2.5	37.54	"	"	90000	-	47	4450	3.0
31.5	6600	2.1	46.43	"	"	90000	-	38	5500	2.6
28.5	7300	2.0	51.70	"	"	90000	-	34.5	6000	2.4
23	9100	1.7	63.49	"	"	90000	-	28	7500	2.1
21	10000	1.6	70.69	"	"	90000	-	25	8400	1.9
18.5	11300	1.45	80.85	"	"	90000	-	22	9500	1.75
16.5	12700	1.3	90.02	"	"	90000	-	20	10500	1.6
14	15000	1.1	107.5	"	"	90000	-	16.5	12700	1.3
12.5	16800	1.0	119.7	"	"	90000	-	15	14000	1.2
10.5	20000	0.84	139.1	"	"	90000	-	13	16100	1.05

P = 30 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
295	970	1.55	4.95	BG70-../D18XA4	312	6900	-	360	790	1.9
250	1140	1.55	5.87	"	"	8200	-	300	950	1.85
205	1390	1.55	7.14	"	"	8800	-	250	1140	1.9
173	1650	1.4	8.48	"	"	9500	-	210	1360	1.7
145	1970	1.15	10.09	"	"	10200	-	175	1630	1.4
122	2300	1.0	11.97	"	"	11200	-	148	1930	1.2
112	2550	0.9	13.08	"	"	11600	-	135	2100	1.1
250	1140	2.3	5.94	BG80-../D18XA4	366	8300	-	300	950	2.8
225	1270	2.3	6.60	"	"	9100	-	270	1060	2.8
176	1620	2.3	8.30	"	"	10400	-	215	1330	2.8
159	1800	2.2	9.21	"	"	10800	-	192	1490	2.6
128	2200	1.9	11.43	"	"	11600	-	154	1860	2.3
116	2450	1.7	12.69	"	"	12400	-	139	2050	2.0
94	3000	1.4	15.62	"	"	13700	-	113	2500	1.7
85	3350	1.25	17.35	"	"	14600	-	102	2800	1.5
74	3850	1.1	19.89	"	"	15500	-	89	3200	1.3
67	4250	0.99	22.09	"	"	16500	-	80	3550	1.2
56	5100	0.82	26.44	"	"	17900	-	67	4250	0.99
134	2100	3.3	10.90	BG90-../D18XA4	458	52300	-	162	1760	4.0
110	2600	2.9	13.37	"	"	55000	-	132	2150	3.5
100	2850	2.7	14.64	"	"	57000	-	121	2350	3.3
82	3450	2.4	17.96	"	"	59800	-	98	2900	2.8
75	3800	2.2	19.67	"	"	62400	-	90	3150	2.7
65	4400	1.9	22.62	"	"	65000	-	78	3650	2.3
59	4850	1.75	24.78	"	"	65000	-	72	3950	2.1
49.5	5700	1.45	29.78	"	"	65000	-	60	4750	1.75
45	6300	1.35	32.62	"	"	65000	-	54	5300	1.6

P = 30 кВт




50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
38.5	7400	1.15	38.21	BG90-../D18XA4	"	65000	-	46.5	6100	1.4
35	8100	1.05	41.85	"	"	65000	-	42.5	6700	1.25
30	9500	0.88	48.82	"	"	65000	-	36.5	7800	1.1
27.5	10400	0.81	53.46	"	"	65000	-	33	8600	0.98
118	2400	3.0	12.45	BG100-../D18XA4	627	72100	-	142	2000	3.6
84	3400	3.0	17.39	"	"	82400	-	102	2800	3.6
61	4650	2.4	23.95	"	"	87900	-	74	3850	2.9
43.5	6500	2.0	33.71	"	"	88500	-	53	5400	2.4
39	7300	1.8	37.54	"	"	90000	-	47	6000	2.2
31.5	9000	1.55	46.43	"	"	90000	-	38	7500	1.9
28.5	10000	1.45	51.70	"	"	90000	-	34.5	8300	1.75
23	12400	1.25	63.49	"	"	90000	-	28	10200	1.5
21	13600	1.15	70.69	"	"	90000	-	25	11400	1.4
18.5	15400	1.05	80.85	"	"	90000	-	22	13000	1.25
16.5	17300	0.97	90.02	"	"	90000	-	20	14300	1.15
14	20400	0.82	107.5	"	"	90000	-	16.5	17300	0.97

P = 37 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
295	1190	1.25	4.95	BG70-...-K/DNF22SB4	521	6900	-	360	980	1.55
250	1410	1.25	5.87	"	"	8200	-	300	1170	1.5
205	1720	1.25	7.14	"	"	8800	-	250	1410	1.55
173	2000	1.15	8.48	"	"	9500	-	210	1680	1.35
250	1410	1.9	5.94	BG80-...-K/DNF22SB4	580	8300	-	300	1170	2.3
225	1570	1.9	6.60	"	"	9100	-	270	1300	2.3
176	2000	1.9	8.30	"	"	10400	-	215	1640	2.3
159	2200	1.8	9.21	"	"	10800	-	192	1840	2.1
128	2750	1.55	11.43	"	"	11600	-	154	2250	1.85
116	3000	1.4	12.69	"	"	12400	-	139	2500	1.7
94	3750	1.1	15.62	"	"	13700	-	113	3100	1.35
85	4150	1.0	17.35	"	"	14600	-	102	3450	1.2
184	1920	3.3	7.97	BG90-...-K/DNF22SB4	671	47900	-	225	1570	4.0
147	2400	2.8	9.95	"	"	50500	-	177	1990	3.4
134	2600	2.7	10.90	"	"	52300	-	162	2150	3.3
110	3200	2.3	13.37	"	"	55000	-	132	2650	2.8
100	3500	2.2	14.64	"	"	57000	-	121	2900	2.7
82	4300	1.9	17.96	"	"	59800	-	98	3600	2.3
75	4700	1.8	19.67	"	"	62400	-	90	3900	2.2
65	5400	1.55	22.62	"	"	65000	-	78	4500	1.85
59	5900	1.4	24.78	"	"	65000	-	72	4900	1.7
49.5	7100	1.2	29.78	"	"	65000	-	60	5800	1.45
45	7800	1.1	32.62	"	"	65000	-	54	6500	1.3
118	2950	2.5	12.45	BG100-...-K/DNF22SB4	842	72100	-	142	2450	3.0
84	4200	2.4	17.39	"	"	82400	-	102	3450	2.9
61	5700	1.95	23.95	"	"	87900	-	74	4750	2.4
43.5	8100	1.6	33.71	"	"	88500	-	53	6600	1.95
39	9000	1.45	37.54	"	"	90000	-	47	7500	1.75
31.5	11200	1.25	46.43	"	"	90000	-	38	9200	1.55
28.5	12300	1.15	51.70	"	"	90000	-	34.5	10200	1.4
23	15300	1.0	63.49	"	"	90000	-	28	12600	1.2

P = 45 кВт



50 Гц			i	Тип	m кг	F _{RN} Н	F _{RV} Н	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
295	1450	1.05	4.95	BG70-...-K/DNF22MB4	551	6900	-	360	1190	1.25
250	1710	1.05	5.87	"	"	8200	-	300	1430	1.25
205	2050	1.05	7.14	"	"	8800	-	250	1710	1.25
250	1710	1.55	5.94	BG80-...-K/DNF22MB4	610	8300	-	300	1430	1.85
225	1910	1.55	6.60	"	"	9100	-	270	1590	1.85
176	2400	1.55	8.30	"	"	10400	-	215	1990	1.9
159	2700	1.45	9.21	"	"	10800	-	192	2200	1.8
128	3350	1.25	11.43	"	"	11600	-	154	2750	1.55
116	3700	1.15	12.69	"	"	12400	-	139	3050	1.4
230	1860	3.2	6.46	BG90-...-K/DNF22MB4	701	44200	-	275	1560	3.8
205	2050	3.0	7.28	"	"	46300	-	245	1750	3.5
184	2300	2.7	7.97	"	"	47900	-	225	1910	3.3
147	2900	2.4	9.95	"	"	50500	-	177	2400	2.8
134	3200	2.2	10.90	"	"	52300	-	162	2650	2.6
110	3900	1.95	13.37	"	"	55000	-	132	3250	2.3
100	4250	1.8	14.64	"	"	57000	-	121	3550	2.2
82	5200	1.6	17.96	"	"	59800	-	98	4350	1.9
75	5700	1.45	19.67	"	"	62400	-	90	4750	1.75
65	6600	1.25	22.62	"	"	65000	-	78	5500	1.55
59	7200	1.15	24.78	"	"	65000	-	72	5900	1.4
118	3600	2.0	12.45	BG100-...-K/ DNF22MB4	872	72100	-	142	3000	2.4
84	5100	2.0	17.39	"	"	82400	-	102	4200	2.4
61	7000	1.6	23.95	"	"	87900	-	74	5800	1.95
43.5	9800	1.3	33.71	"	"	88500	-	53	8100	1.6
39	11000	1.2	37.54	"	"	90000	-	47	9100	1.45
31.5	13600	1.05	46.43	"	"	90000	-	38	11300	1.25